



TFP200 DECK SCALER

The TFP200 Deck Scaler is designed for the effective removal of coatings and corrosion from ship decks, hatches, and tank tops. Its rigid steel chassis provides a strong, stable platform for precise surface preparation. Available in pneumatic, battery, petrol and electric models, the TFP200 range offers flexible power options to suit different working environments. A wide selection of attachments allows the scaler to handle everything from light cleaning to heavy descaling, ensuring versatility, efficiency, and consistent results across a variety of marine maintenance tasks.



WHAT ARE THE MAIN ADVANTAGES OF OUR TFP200 DECK SCALER?



DEPTH CONTROL

The TFP200 allows you to control machine height, meaning you only remove the top layer of coating or corrosion minimizing any risk of deck damage.



COATING REMOVAL

The TFP200 is suitable for light, medium and heavy coating removal. You can select a drum dependant on the required finish or profile you seek to achieve



EXPERTISE

Trelawny works with major fleet owners on a global basis and with combined expertise, we achieve exceptional profiles whilst providing long lasting quality



CONSUMABLE LIFESPAN

Trelawny consumables typically cover 750–1,000 m² per unit. Comparable alternative brands average around 300 m² per drum. This longer lifespan helps increase productivity and reduce costs over time.



COATING & CORROSION REMOVAL



IDEAL FOR DECK MAINTENANCE



DUST FREE DESCALING



FEATURES & BENEFITS

- Production rates up to 30m² per hour.
- Adjustable hand-wheel for depth control.
- Angled TVS® dust port for virtually dust free working.
- Isolation safety switch to ensure operator safety.
- Quick change cutter drum and consumables.



APPLICATIONS

- Fast removal of coatings and corrosion.
- Open deck areas, tank tops and hatch covers.
- Pre-preparation of thick coatings before high pressure or shot blasting operations.
- Oil platform and heli deck descaling.
- Removal of deposits from previous cargos.

TECHNICAL DATA

Model	Trelawny Part No.	IMPA Part No.	ISSA Part No.	Power Source	Power kw (HP)	Voltage	Frequency (Hz)	Cutter Speed (RPM)	Weight (Kg)	Plug	Air Consumption (lps - cfm)
TFP200 Petrol	320.2400T	-	-	Petrol	4.1 (5.5)	-	-	1833	64	-	-
TFP200 110v TCT	320.2402T	-	-	Corded Electric	2.2 (3)	110	50 / 60	1650	71	IEC Industrial 32 Amp 3 pin	-
TFP200 230v TCT	320.2404T	59.22.36	55.096.03	Corded Electric	2.2 (3)	230	50 / 60	1650	71	IEC Industrial 16 Amp 3 Pin	-
TFP200 400v TCT	320.2406T	59.22.37	55.096.04	Corded Electric	2.2 (3)	400	50 / 60	1650	71	IEC Industrial 16 Amp 5 Pin	-
TFP200 110v TCT 60Hz	320.2416T	59.22.35	55.096.05	Corded Electric	2.2 (3)	110	60	1650	71	IEC Industrial 32 Amp 3 pin	-
TFP200 Air TCT	320.2412T	59.22.31	55.096.01	Compressed Air	2.6 (3.5)	-	-	1528	62	-	78 - 165

TECHNICAL DATA - TRELAUNY VOLTMAX

Model	Trelawny Part No.	Weight (Kg)	Power (HP-Kx)	Voltage (V)	Cutter Speed (RPM)	Runtime (Mins)	Charge Time (Mins)	Vibration Level (Aeq m/s²)
TFP200-VM Battery Powered Motor	320.2520T	58	2.2	82	2800	35	-	4.4
TFP200-VM Motor, 2 x Batteries & Charger	320.2528T	66	2.2	82	2800	35	50	4.4