

LPS55

POLE SCABBLER



The LPS55 is a powerful long reach scabbler for vertically preparing hard to reach areas.

At 14 metres in length it allows scabbling below the reinforcement bar.

The powerful blows quickly remove concrete without damaging the underlying substrate.

FEATURES

- Replaceable pin fit carbide tipped scabbling heads
- Long handle for extended reach into inaccessible areas
- Angled air inlet to direct hose away from operator
- Hand guard to protect operator

APPLICATIONS

- Heavy scabbling of hard to access areas such as below re-inforcement bars and between shuttering
- Scabbling of corners, edges and joints
- Fast removal of material
- Aggressive keying without damaging the substrate



Scabbling Concrete



Concrete Removal



Preparing Joints

KEY CONSUMABLES & ACCESSORIES

Image	Part Number	Description
	441-5359	Scabbling Head 5 Point TCT Bush Pin fit - including pin Rough pitted profile, ideal for application of fresh concrete or coatings
	441-5369	Scabbling Head 9 Point TCT Bush Pin fit - including pin Rough pitted profile, ideal for application of fresh concrete or coatings
	441-5360	Scabbling Head Cruciform Pin fit - including pin Flatter surface profile, ideal for fast reduction of material
	450-5017	Round Foot Compactor - 127 mm (5" Round) Pin fit
	450-5011	Square Foot Compactor - 100 x 100mm (4" x 4") Pin fit
	450-5013	Compactor Foot - 152 x 127mm (6" x 5") Pin fit
	450-5016	Compactor Foot - 100 x 200mm (4" x 8") Pin fit
	859-1580	3/4" BSP Inline Lubricator
	458-1580	Whip Hose & Oiler Assembly Consists of whip hose, whip check and 3/4" lubricator
	843-0752	3/4" Air Hose Complete with couplings 15m length
	815-5550	Whip Check
	446-5000	Service Kit consists of: Bush TCT Pin Fit with Pin (1each), Valve Stem (1each), Spring Seat (1each) Spring Valve (1each), Valve Stem Seal O'Ring (1each), Valve Stem Seal O'Ring (1each) Centre Bar O'Ring (1each), Piston Roll Pin (1each), Wiper Seal (1each)

TECHNICAL DATA

Model	Part Number	Weight (kg)	Length (mm)	Blows per minute (BPM)	Air Consumption (lps - cfm)	Vibration Level (Aeq m/s ²)
LPS55 c/w 5 Point Scabbling Head	150-5001	134	1392	1300	11.6 - 24.6	38.60
LPS55 c/w 9 Point Scabbling Head	150-5002	134	1392	1300	11.6 - 24.6	38.60
LPS55 c/w 5" Round Compactor Foot	150-5031	134	1392	1300	11.6 - 24.6	38.60
LPS55 c/w 4" x 4" Compactor Foot	150-5030	134	1392	1300	11.6 - 24.6	38.60
LPS55 c/w 6" x 5" Compactor Foot	150-5021	134	1392	1300	11.6 - 24.6	38.60