




SF

SCALEFORCE PNEUMATIC HANDHELD SCALING HAMMERS



Requires compressor: 5.2lps - 11cfm capable

-  Low vibration options available
-  Dust control options available
-  ATEX options available

Trelawny's SF range of scaling hammers are highly effective for quick removal of heavy scale and coatings.

The SF1/VLSF1 single head tools are perfect for smaller and awkward to reach areas, being lightweight and easy to handle. It's perfect for reaching behind structures and up against bulkheads.

The SF3 three head tools give faster production for more open areas.

Safety built in as standard.

FEATURES

- Option of replaceable carbide tipped scaling heads or economical hardened steel single piece pistons
- Beryllium copper spark resistant heads for use in potentially explosive environments
- Ergonomic handle for ease of use - also available with a short handle and/or inline for tight areas
- Simple and robust design for low and easy maintenance

APPLICATIONS

- Quick removal of heavy coatings and rust
- Preparation before blasting
- Cleaning pipes



Thick Paint Removal














Heavy Duty Descaling



Rust Removal

KEY CONSUMABLES & ACCESSORIES

Image	Part Number	Description	Image	Part Number	Description
	426.5351	Cruciform Taper fit Cutter Head Tungsten carbide tipped head - for fracturing and removal of coatings		458.1555	Whip Hose & Oiler Assembly Consists of whip hose, whip check and 1/2 inline lubricator
	606.5303	Cruciform Taper fit Cutter Head Beryllium copper spark resistant - for fracturing and removal of coatings		421.3452	Whip Hose Consists of air hose 3/8" BSP clar - 2m
	426.5352	Bush Hammer Taper fit Cutter Head Tungsten carbide tipped head - creates a heavier key on the surface		815.5550	Whip Check
	612.5301	Piston to fit Cutter Heads		614.5301	Brush Seal
	859.1555	1/2 Inline Lubricator		446.1520	SF1 Service Kit
				446.1530	SF3 Service Kit

TECHNICAL DATA

Model	Part No.	Consumable (type of head)	Weight (kg)	Length (mm)	Working height (mm)	Blows per minute (BPM)	Air consumption (lps - cfm)	Noise level (db (A))	Vibration Level (Aeq m/s ²)
Vibro-Lo™ Single Head	196.5095	Cruciform head	2.5	515	140	3000	4.25 - 9	92.5	3.7
Triple Head	153.5300	Cruciform head	3.7	450	152.5	3000 x 3	5.2 - 11	92.7	13.4
VLSF1-EX Single Head	196.5110	Beryllium copper taper fit cutter	2.5	515	140	3000	4.25-9	92.5	3.7
SF3-EX Triple Head	153.5310	Beryllium copper taper fit cutter	3.7	450	152.5	3000 x 3	5.2 - 11	92.7	13.4