

SH RANGE



Low vibration options available



Dust control options available

The SH1 and VL SH1 single head scabblers are the ideal tools for roughening and preparing concrete in small areas such as concrete joints.

The VLSH1 low vibration model helps reduce the risk to operators of vibration related injuries.

The SH3 triple head scabblers are the ideal tools for roughening and preparing concrete in larger areas such as walls and columns.

The optional TVS® vacuum shroud allows the connection of an industrial dust collector for collecting nuisance and hazardous dust for protection of operators and environment.

Safety built in as standard.

FEATURES

- Replaceable tough carbide tipped piston for fast production and long service life
- Side handle on triple models for greater control
- Triple headed models can be used in two configurations, the optional in-line position aiding access to prepare narrow joints.
- Short & in-line models available
- Simple and robust design for low and easy maintenance
- TVS® dust shrouded models available

APPLICATIONS

- Removal of laitance
- Roughening and exposing aggregate
- Preparing joints and cracks
- Removing coatings
- Reduction and levelling



Reducing Levels on Concrete



Roughening Concrete



TVS® Dust Shroud

KEY CONSUMABLES & ACCESSORIES

Image	Part Number	Description	
	612.5320	Single Piece Cruciform Piston Flatter surface profile, ideal for fast reduction of material	
	612.5325	Single Piece Bush Piston Rough pitted profile, ideal for application of fresh concrete or coatings	
	446.1620 446.1625	SH1 Service Kit (Cruciform/Bush Piston) Consists of: - Valve Cap O'Ring, Valve Spring, Valve Stem, Valve Seat O'Ring, Throttle Lever, Spring Pin (1 each) - Screwed Cap, Compression Spring, Cap Spring, Brush Seal, Piston (1 each)	
	446.1630 446.1635	SH3 Service Kit (Cruciform/Bush Pistons) Consists of: - Valve Cap O'Ring, Valve Spring, Valve Stem, Valve Seat O'Ring, Throttle Lever, Spring Pin (1 each) - Screwed Cap, Compression Spring, Cap Spring, Brush Seal, Piston (3 each)	
	437.5100	SH1 Vacuum Shroud * Not available for low vibration models	
	437.5300	SH3 Vacuum Shroud	
	859.1555	½" BSP Inline Lubricator	
	458.1555	Whip Hose & Oiler Assembly Consists of Whip Hose, Whip Check and ½ Inline Lubricator	
	421.3452	Whip Hose Consists of Air Hose 3/8" BSP Claw - 2m	
	815.5550	Whip Check	

TECHNICAL DATA

Model	Part Number	Weight (kg)	Length (mm)	Working Height (mm)	Blows Per Minute (BPM)	Air Consumption (lps - cfm)	Noise Level (db (A))	Vibration Level (Aeq m/s²)
Low Vibration Single Scabblers Bush Hammer Head	196.5105	2.5	515	160	2900	4.25 - 9	91	4.50
Low Vibration Single Scabblers Cruciform Head	196.5100	2.5	515	160	2900	4.25 - 9	91	4.50
Single Scabblers Cruciform Head fitted with shroud	139.5192	2.7	485	160	2400	3.7 - 8	94	6.96
Triple Scabblers Side Handle Bush Hammer Head	153.5250	5.2	450	160	2400 x 3	7 - 15	98	8.7
Triple Scabblers Side Handle Cruciform Head	153.5200	5.2	450	160	2400 x 3	7 - 15	98	8.7
Triple Scabblers with Shroud Cruciform Head Short Handle	139.5390	5.2	380	160	2400 x 3	7 - 15	98	8.7
Triple Scabblers with Shroud Cruciform Head	139.5392	5.2	450	160	2400 x 3	7 - 15	98	8.7