

TFP260

FLOOR SCARIFIER

Productivity:
Ave 35 Square
Meters per
hour at 5mm
per pass



Reducing Levels on Concrete



Roughening Concrete



Use with A45 Dust Collector

TVS Dust control options available

The TFP260 is a heavy duty machine for medium to large jobs.

Increased weight and power give exceptional performance for a machine in this segment.

Robust chassis construction and a heavy duty double web cutter drum ensure the TFP260 keeps working on the toughest of surface preparation jobs.

The quick lift drum mechanism gives additional control to the operator.

FEATURES

- 250mm cutting width
- Tough 8mm welded steel construction for added weight and strength
- Precise screw type height adjustment with quick lift drum lever for accurate working and operator control
- Angled dust port allows connection of industrial dust collector giving virtually dust free performance
- Rear mounted electrical switchgear utilizing vibration resistant components

APPLICATIONS

- Suitable for medium to large jobs
- Removal of hard coatings
- Levelling and removing layers of hard materials
- Removing painted lines

KEY CONSUMABLES & ACCESSORIES

Image	Part Number	Description
	320.7009	Tungsten Carbide Tipped Cutters For all concrete texturing, scabbling, planing and grooving applications
	326.3658	Star Cutters For the removal of paint, coatings and laitance. Deck Descaling
	326.5120	Beam Cutters For the removal of paint, coatings, laitance, grease, dirt and ice deposits. Deck Descaling
	320.5680	Milling Cutters For the removal of thermoplastic road and runway markings, bituminous and rubber deposits.
	320.4160	Spacers Used to create a gap in between cutters.

- Note: Please see page 26 for detailed information on the full TFP260 accessories range.

TECHNICAL DATA

Model	Part Number	Weight (Kg)	Power (HP - kW)	Voltage (v)	Cycle (Hz)	Cutter Speed (RPM)	Plug Size	Recommended Cable Size (CSA) (mm)	Recommended Cable Length (m)	Engine Type	Vibration Level (Aeq m/s ²)
TFP260 Petrol	326.2400T	1475	8 - 6	-	-	1850	-	-	-	Honda GX240	8.8
TFP260 400v	326.2406T	1475	75 - 5.5	400	50/60	1850	16 Amp 5 pin	4mm	40m	-	2.4

DIMENSIONS

Working Width (mm)	Length (mm)	Width (mm)	Height (mm)	Maximum Cutting Depth (mm)	Working Distance from Wall (mm)	Vacuum Take Off Diameter (mm)
250	1010	480	1080	6	75	50

All part numbers specified above are for machines complete with 8 point tungsten carbide tipped (TCT) cutters. For machines requiring alternative cutting media please specify.