

# TVS® DUST CONTROL



Low vibration options available



Dust control options available



ATEX Certified

Trelawny Tool & Vacuum system (TVS) Shrouded needle scalers are designed for the dust-free safe removal of hazardous materials such as lead, asbestos and silica dust.

In combination with our K series HEPA dust collectors they form a high performance safety focussed system for hazardous abatement and remediation applications.

**Requires compressor:  
3.8lps - 8cfm  
capable**

## FEATURES


- Available in low vibration models and B Series tools
- TVS shrouds are retrofittable to all needle scaler models
- Cuffs for flat, edge, and corner applications
- Adjustable for access
- Low air consumption
- Simple maintenance with no special tools
- Available as a needle or chisel scaler for multiple applications
- Unique design, valveless and oversized piston

## APPLICATIONS

- Removal of coatings, corrosion and other accumulated materials
- Slag removal and stress relieving welds
- Cleaning mixers, formwork and machinery
- Spot repairs
- Cleaning concrete for repair



Dust-free Descaling



Use with K Series Vacuum



Cuffs for a Range of Applications

## KEY CONSUMABLES & ACCESSORIES

Image	Trelawny Part No.	Description
	418.2003	VL203/223 TVS shroud
	418.3003	VL303 TVS shroud
	418.2200	2B/BPG TVS shroud
	418.3040	3BPG TVS shroud
	731.2101	VL203/223 2B/BPG Corner cuff
	731.2102	VL203/223 2B/BPG Edge cuff
	731.2103	VL203/223 2B/BPG Flat cuff
	731.3101	VL303/3BPG Corner cuff
	731.3102	VL303/3BPG Edge cuff
	731.3103	VL303/3BPG Flat cuff

For additional spares and accessories please refer to page 45 for VL models and page 47 for B/BPG series models

## TECHNICAL DATA

Model	Trelawny Part No.	Type	Needle Quantity	Weight (kg)	Blows per Min (BPM)	Air Consumption (lps - cfm)	Air Inlet Size (BSP)	Overall Length (mm)	Noise Level (LwA db(A))	Vibration Level (Aeq m/s <sup>2</sup> )
VL223 TVS	139.2103	In-line	19	2.35	2400	1.89-4	¼	370	90.7	2.56
VL203 TVS	139.2003	Pistol Grip	19	2.7	2400	1.89-4	¼	340	90.7	2.75
VL303 TVS	139.3003	Pistol Grip	28	3.51	3000	2.6 - 5.5	¼	370	109.5	2.3
VL223Ex TVS	139.2423	In-line	19	2.35	2400	1.89 - 4	¼	370	90.7	2.56
VL203Ex TVS	139.2403	Pistol Grip	19	2.7	2400	1.89 - 4	¼	340	90.7	2.75
VL303Ex TVS	139.2433	Pistol Grip	28	3.51	3000	2.6 - 5.5	¼	370	109.5	2.3
3BPG TVS	139.3197	Pistol Grip	28	3.7	2200	3.8 - 8.0	¼	343	105.1	18.9

For K series dust collectors and accessories please see page 76

SCABBING  
SCARIFYING  
GRINDING & POLISHING  
SURFACE STRIPPING  
INDUSTRIAL  
DUST CONTROL  
VINYL WRAPPING