

# VL LRS55

## POLE SCABBLER



Low vibration options available

The VL LRS55 is a powerful long reach scabbler for vertically preparing hard to reach areas.

At 1.3 metres in length it allows scabbling below the reinforcement bar.

The powerful blow quickly removes concrete without damaging the underlying substrate.

Vibro-Lo™ low vibration system fitted as standard, helping to reduce risks to operators of vibration related injuries.

Safety built in as standard.

### FEATURES

- Replaceable pin fit carbide tipped scabbling heads
- Long handle for extended reach into inaccessible areas
- Angled air inlet to direct hose away from operator
- Hand guard to protect operator

### APPLICATIONS

- Heavy scabbling of hard to access areas such as below re-inforcement bars and between shuttering
- Scabbling of corners, edges and joints
- Fast removal of material
- Aggressive keying without damaging the substrate



Scabbling Concrete



Concrete Removal



Texturing Concrete

### KEY CONSUMABLES & ACCESSORIES

Image	Part Number	Description
	441.5359	Scabbling Head 5 Point Bush Pin fit - including pin Rough pitted profile, ideal for application of fresh concrete or coatings
	441.5369	Scabbling Head 9 Point Bush Pin fit - including pin Rough pitted profile, ideal for application of fresh concrete or coatings
	441.5360	Scabbling Head Cruciform Pin fit - including pin Flatter surface profile, ideal for fast reduction of material
	446.5000	VL LRS55 Service Kit Consists of: - Valve Spring, Valve Seat O'Ring, Throttle Lever Roll Pin, Thrust Ring, Circlip, Spring, (1each) - Piston O'Ring, Wiper Seal, Valve Stem O'Ring, Piston Roll Pin (1 each) - Locking Pin, Centre Bar O'Ring (2 each)
	859.1580	3/4" BSP Inline Lubricator
	458.1580	Whip Hose & Oiler Assembly Consists of whip hose, whip check and 3/4" lubricator
	843.0752	3/4" Air Hose Complete with couplings 15m length
	815.5550	Whip Check

### TECHNICAL DATA

Model	Part Number	Weight (kg)	Length (mm)	Blows per minute (BPM)	Air Consumption (lps - cfm)	Vibration Level (Aeq m/s <sup>2</sup> )
VL LRS55 c/w 5 Point Scabbling Head	150.5320	21.5	1270	1300	11.6 - 24.6	4.2
VL LRS55 c/w 9 Point Scabbling Head	150.5321	21.5	1270	1300	11.6 - 24.6	4.2

Note: Can be converted to a pole compactor by changing the scabbling head with a tamper foot.